

Technical Data Sheet 03.06.2019 - p. 1/2

Master Colour Oil provides colour and protection in one product. The oil penetrates the wood and ensures a hardwearing surface with high resistance to water and dirt. It is perfect for indoor use on all unfinished, new or newly-sanded surfaces in all wood species.

- · Resistant to dirt and fluids, e.g. water, coffee, tea and red wine
- Available in many different colours
- Gives the wood a beautiful, breathable surface
- Indoor climate labelled



Application area

For untreated, new or newly-sanded wooden surfaces.

Work description

Final sanding

Preparation Product, room and floor temperature must be between 15-30°C. Wood humidity must not exceed 12%.

Ensure good ventilation during application and when drying. The wood must be newly sanded, use grit 100-120 for the final sanding. Vacuum thoroughly. Clean the wood with WOCA Intensive Wood Cleaner and leave it to dry for at least 8 hours before applying the oil.

Always remember to test on a less visible spot to check the compatibility of the surface with the

product.

Treatment Thoroughly shake the container of Master Colour Oil, both before and during use. Containers with

different batch numbers should be mixed to avoid colour mismatch. Apply the oil using a short-bristled paint roller (3-4 mm) in an even coat. Work in small areas of no more than 10 m² at a time. Leave the oil to soak in for 10-20 min. If the oil soaks quickly into the wood, apply more oil. Polish the oil into the wood until the surface appears saturated. Use a buffing machine with a beige pad for large areas and a polishing cloth/pad manually for small areas. Remove excess oil with dry, lint-free cotton cloths or pads until the surface no longer appears wet. Continue until the whole area has been polished and excess oil has been thoroughly removed. To ensure a good saturation the surface should be re-polished with 1 dl Master Colour Oil per 10 m2 within 6-12 hours after the first application. The oil should be polished

thoroughly, as described earlier.

Note Do not expose the surface to water or clean it for the first 7 days while the oil is hardening. After 7 days

the floor can be cleaned with WOCA Natural Soap, which gives the surface extra protection.

Drying time

Drying time 12-24 hours at 20°C

Fully hard 5-7 days at 20°C and 55% humidity

Grit 100-120



Technical data

Binder Vegetable oil components

Density 0.90-0.95 g/ml Solid content Approx. 60 %

Shelf life 3 years

Application Temperature 15-30°C

Coverage (diluted) Approx. 8-10 m2/L, depending on wood type and

surface

Colours 11 colours

Cleaning of tools With WOCA Solvent or turpentine.

Storage + 10-25°C. Keep out of reach of children. Must not be

exposed to heat (e.g. sunlight). Store frost-free.

VOC This product contains max. 370 g VOC/I. Permitted value

is 500 g VOC/I (cat.A/i).

Packaging 1L - 2.5 L - 5 L

Migration test of nondesired materials EN 71-3:2013

Authorisations Danish Indoor Climate Labelling

IBR: TVOC28/A+, GIS: Ö60

Maintenance and related products

Weekly cleaning Natural Soap, article no. 511010A

Monthly care Oil Refreshing Soap, article no. 511210A

Re-oiling Maintenance Oil, article no. 527310A/527410AA

Maintenance Gel, article no. 527802A/527902A

Related products Intensive Wood Cleaner, article no. 551525

Accessories Paint Roller, 4 mm luv, article no. 88004

Paint roller handle, 25mm, article no. 599650

Telescopic rod, article no. 599651

Contact

WOCA Denmark A/S

Tværvej 6

DK - 6640 Lunderskov T +45 9958 5600

info@wocadenmark.com wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description

replaces all previous versions.